

Discrete Optocouplers

8018630000

When good enough just isn't good enough

Weidmüller 

DK40 / 35 for TS 35

[Email to a Friend](#)[View Line Drawing](#)

Representative Photo

Technical Information

Rail Type	TS 35
Input Voltage	5 VDC
Module Type	Terminal Block
Number of Channels	1
Maximum Output Current	20 mA
LED Color	Green
Housing Type	DK40/35

Additional Data

Positive/Negative Switching Type	Positive
Input Current	10 mA
Power Consumption (Watts/DC)	50 mW
Turn ON (Voltage/Current)	2.4 VDC
Operative Time ON	15 µs
Operative Time OFF	70 µs
Status Indicator (LED)	Green
Voltage Output	5...48 VDC
Switching Current Minimum	5 mA
Voltage Drop at Maximum Current Rating	1.6 V
Switching Frequency Maximum	20 Hz
Dielectric Strength Input to Output	3.75 kV _{eff} / 5.3 kV DC
Dielectric Strength Terminals to DIN-Rail	4 kV _{eff}
Storage Temperature Range	-40°C...+85°C
Operating Temperature Range	-25°C...+50°C
Wire Size	#20...12 AWG 0.5...2.5 mm ²
Clamp Screw Tightening Torque Nm (lb.in.)	0.5 (4.38)
Mechanical Dimensions (WxLxH) mm (in.)	6/65/57 (.24"/2.56"/2.24")
Insulation Stripping Length mm (in.)	9 (.35")

Polarity Protection	No
Certifications	CE

Suggested Accessories

DIN-rail

End bracket

End plate/partition (AP/TW)

Ferrules

Markers (SchT)

Marking pens

Marking tags (DEK)

Mounting brackets

QB jumpers

Tools

Product Liability The above information describes our products. It does not constitute guaranteed properties and is not intended to affirm the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot be completely ruled out. Technical data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from:

Weidmüller - North America
United States 001 (800) 849-9343
Canada 001 (800) 268-4080

or

Weidmüller - Germany
Telephone operator 0049 (-5252) 960-0