

**DK-SERIES
DKO 35 24VDC E:U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



At just 6 mm wide, all components of the DKO range of minicouplers have an extremely narrow design.

Four or five screw connections with a nominal cross-section of 4 mm² are available.

The minicouplers are suitable for a wide range of applications in the coupling of digital sensor/actuator signals with automation devices and the process field.

General ordering data

Type	DKO 35 24VDC E:U
Order No.	8181990000
Version	DK-SERIES, Solid-state relay, Rated control voltage: 24 V DC $\pm 10\%$, Rated switching voltage: 24 VDC $\pm 10\%$, Rated switching current: 2 A, Screw connection
GTIN (EAN)	4008190277017
Qty.	5 pc(s).

DK-SERIES
DKO 35 24VDC E:U

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	12 mm	Height	65 mm
Depth	56 mm	Net weight	28.6 g

Temperatures

Humidity	40 °C / 93 % rel. humidity, no condensation	Operating temperature	-25 °C...+40 °C
Storage temperature	-40 °C...+85 °C		

Probability of failure

MTTF	1,239 Years
------	-------------

control side

Rated control voltage	24 V DC $\pm 10\%$	Power rating	Max. 290 mW
Input frequency	100 Hz	Cut-in (switch-on) voltage	approx. 18 V DC
Rated auxiliary voltage	No		

Load side

Solid-state type	Transistor	Rated switching voltage	24 VDC $\pm 10\%$
Continuous current	2 A	Rated switching current	2 A
Switch-on delay	2 ms	Switch-off delay	< 7 ms
Protective circuit, load side	Varistor	Load side status indicator	LED green
Short-circuit-proof	Yes	Rated auxiliary voltage	No
Pulse duty factor (gen.)	1:2		

General data

Solid-state type	Transistor	No. of poles	1
Wire connection method	Screw connection	Humidity	40 °C / 93 % rel. humidity, no condensation
Standards	DIN EN 50178	Wire cross-section, solid, max.	4 mm ²
Wire connection cross section, finely stranded, max.	4 mm ²		

Insulation coordination

Rated voltage	300 V	Clearance and creepage distances for control side - load side	≥ 3 mm
Impulse withstand voltage	4 kV	Pollution severity	2
Surge voltage category	III		

Further details of approvals

Standards	DIN EN 50178
-----------	--------------

DK-SERIES DKO 35 24VDC E:U

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Connection data

Clamping range, rated connection	4 mm ²	Clamping range, rated connection, max.	4 mm ²
Clamping range, rated connection, min.	0.5 mm ²	Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²	Wire connection method	Screw connection
Wire cross-section, solid, max.	4 mm ²	Wire cross-section, solid, min.	0.5 mm ²

Classifications

ETIM 3.0	EC001504	UNSPSC	30-21-18-01
eClass 5.1	27-27-09-90	eClass 6.2	27-14-11-20
eClass 7.1	27-14-11-20		

Product information

Descriptive text ordering data	Input at bottom
Descriptive text accessories	End plate AP DKT 4: 0687560000

Approvals

Approvals



ROHS Conform

Downloads

Declaration of Conformity [K072_08_09.pdf](#)
[3-D model](#)