

SEE ESD 120

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



Weidmüller offers a selection of ESD pliers, for use in the electronics and precision-mechanics sectors.

What does ESD mean?

Electrostatic discharge can damage micro-electronic components. In proportion to their dimensions, the energy of a electrostatic discharge in a semiconductor can be compared to a lightning strike on a tree. Thus the ESD pliers grip are made of additional materials which are very non-conductive. The static charge is then discharged harmlessly. Only by with working with ESD pliers can you guarantee that no sensitive electronic components are damaged. You also guarantee compliance with the relevant standards and regulations(for example, IEC TR 61 340-5, DIN EN 61 340-5, and SP Method 2472). The two-coloured multi-component grips are ergonomic and optimized for motion patterns during repair work. The shape and material provide a sure grip and reduce fatigue during work. Force is distributed over a larger contact area, resulting in a distribution of the pressure.

General ordering data

Туре	SEE ESD 120		
Order No.	<u>9205130000</u>		
Version	Electronic ESD diagonal-cutting pliers with pointed head		
GTIN (EAN)	4032248698936		
Qty.	1 pc(s).		



SEE ESD 120

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Width	120 mm	Width (inches)	4.724 inch
Weight	90 g	Net weight	65.6 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Pliers

Conductor diameter, max. (H)	1.5 mm	Protective insulation, 1000 V	No	
Shape (diagonal-cutting pliers)	tapered head	Total length	120 mm	

Classifications

ETIM 6.0	EC000165	ETIM 7.0	EC000165
eClass 9.0	21-04-37-11	eClass 9.1	21-04-37-11
eClass 10.0	21-04-37-11	UNSPSC	23-17-16-04

Approvals

Approvals



Downloads

Brochure/Catalogue CAT 9 IETH 18/19 EN
CAT 6 TOOLS 15/16 EN