

# TLI-1550HC



## Tadiran Lithium Ion High Capacity

### Electrical characteristics (for batteries stored at RT for 1 year or less)

Max. Capacity when charge to 4.1 V (discharged @ 20 mA to 2.2 V at 20 °C)	500 mAh
Discharge end voltage	2.2 V (discharge below 2.2 V at 20 °C may increase the TLI internal impedance)

### Mechanical characteristics

Length	52.0 +0/-1 mm
Diameter	15.1 mm. max
Weight	18.8 gr. max

### Operating conditions

Max continuous discharge current at 20 °C	4.0 A (without PTC)
Charge (Constant Current Constant Voltage method)	
Max. charge voltage	4.1 V
Max. charge current at -20 °C ÷ +50 °C	120 mA
Max. charge current at -40 °C ÷ +85 °C	20mA
Charge/discharge operating temperature	-40 °C ÷ +85 °C
Charge/discharge cycles (charge 250 mA to 4.1 V EOC 20 mA, discharge 200 mA to 2.5 V at 20 °C)	> 500
Reversible Retention Capacity after 100 cycles (discharge at 100 mA at 20 °C)	93%
Reversible Retention Capacity after 5 years (discharge at 100 mA at 20 °C)	91%
Cell impedance at RT	< 100 mΩ at 1 kHz

### Safety

	Tested according to:
Short circuit at RT and at +55 °C	UL, UN, IEC
Thermal abuse at +130 °C	UL, IEC
Overcharge & Forced Discharge	UL, UN, IEC
Impact	UL, IEC
Crush	UL, UN, IEC
Shock and vibration	UL, UN, IEC
Temperature Cycling	UL, UN, IEC

UN Manual of Tests and Criteria 38.3, UL 1642, IEC 62133

### Warning:

Fire, Explosion, And Severe Burn hazards. Do Not Crush,  
Disassemble, Heat Above 100°C, Short Circuit, Incinerate or Expose  
Contents to Water.



### Technology

- ☒ Anode: Carbon based
- ☒ Cathode: Multi metal oxides
- ☒ Electrolyte: Organic
- ☒ Shut down separator

### Key Features

- ☒ Wide operating temperature range
- ☒ High number of charge/discharge cycles
- ☒ Low self-discharge - long operating life
- ☒ Hermetically sealed (glass-to-metal)
- ☒ High reliability
- ☒ Lightweight
- ☒ Safe design

### Main Applications

- ☒ Energy Harvesting
- ☒ Asset, Container & Cargo Tracking
- ☒ Automotive Emergency Call
- ☒ Internet of things (IOT)
- ☒ Electrical grid monitoring
- ☒ Parking Meter
- ☒ BUB in metering

### Ordering Part No.

- ☒ TLI-1550HC/Z2/T 61-1553-14200
- ☒ TLI-1550HC/Z2/TP 61-1553-14300

For TLI-1550HC w/o PTC please  
contact Tadiran Batteries Ltd.

### Tadiran Batteries Ltd.

44 Yitzhak Rabin Boulevard  
Kiryat Ekron 76950, Israel  
Tel: +972 (8) 944-4555  
Fax: +972 (8) 941-3079

[www.tadiran.com](http://www.tadiran.com)


THE INFORMATION PROVIDED HERE IS NECESSARILY OF A GENERAL NATURE. SINCE SPECIFIC PERFORMANCE DEPENDS ON ACTUAL OPERATING AND STORAGE CONDITIONS, OUR ENGINEERS WILL PROVIDE PARTICULAR APPLICATION INSTRUCTIONS UPON REQUEST. DATA SUBJECT TO REVISION WITHOUT NOTICE. ANY REPRESENTATION IN THIS BROCHURE CONCERNING PERFORMANCE ARE FOR INFORMATION PURPOSES ONLY AND NOT WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF FUTURE PERFORMANCE. TADIRAN'S STANDARD LIMITED WARRANTY, STATED IN ITS SALES CONTRACT OR ORDER CONFIRMATION FORM IS THE ONLY WARRANTY OFFERED BY TADIRAN.

# TLI-1550HC




## Performances data


Discharge Curves at 20 °C




Discharge Curves at 1 A




10 Sec. Pulse Capability at RT




1 Sec. Pulse Capability at 1A



Charge/ Discharge Cycling Performance at RT \*



OCV vs. Capacity





THE INFORMATION PROVIDED HERE IS NECESSARILY OF A GENERAL NATURE. SINCE SPECIFIC PERFORMANCE DEPENDS ON ACTUAL OPERATING AND STORAGE CONDITIONS, OUR ENGINEERS WILL PROVIDE PARTICULAR APPLICATION INSTRUCTIONS UPON REQUEST. DATA SUBJECT TO REVISION WITHOUT NOTICE. ANY REPRESENTATION IN THIS BROCHURE CONCERNING PERFORMANCE ARE FOR INFORMATION PURPOSES ONLY AND NOT WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF FUTURE PERFORMANCE. TADIRAN'S STANDARD LIMITED WARRANTY, STATED IN ITS SALES CONTRACT OR ORDER CONFIRMATION FORM IS THE ONLY WARRANTY OFFERED BY TADIRAN.

# TLI-1550HC






## Lead termination

TLI-1550HC/Z2/T 61-1553-14200



TLI-1550HC/Z2/TP 61-1553-14300



THE INFORMATION PROVIDED HERE IS NECESSARILY OF A GENERAL NATURE. SINCE SPECIFIC PERFORMANCE DEPENDS ON ACTUAL OPERATING AND STORAGE CONDITIONS, OUR ENGINEERS WILL PROVIDE PARTICULAR APPLICATION INSTRUCTIONS UPON REQUEST. DATA SUBJECT TO REVISION WITHOUT NOTICE. ANY REPRESENTATION IN THIS BROCHURE CONCERNING PERFORMANCE ARE FOR INFORMATION PURPOSES ONLY AND NOT WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF FUTURE PERFORMANCE. TADIRAN'S STANDARD LIMITED WARRANTY, STATED IN ITS SALES CONTRACT OR ORDER CONFIRMATION FORM IS THE ONLY WARRANTY OFFERED BY TADIRAN.